

MAILBOX TURNOUT WITH CURB AND GUTTER DETAIL




SECTION A-A

- 1) COMBINATION CURB AND GUTTER, TYPE B-6.24
- BITUMINOUS BASE COURSE, 6" (PE) OR BITUMINOUS BASE COURSE, 8" (CE)
- (3) INCIDENTAL BITUMINOUS SURFACING, 2"
- 4 CONCRETE CURB TYPE B
- BITUMINOUS CONCRETE SURFACE COURSE, SUPERPAVE MIX "D", N70, 11/2"
- 6 BITUMINOUS CONCRETE BINDER COURSE, SUPERPAVE, IL-19.0, N70, 11/2"
- 7) AGGREGATE SUBGRADE, 12"



MAILBOX ON NEARSIDE OF ENTRANCE, SHOULDER SECTION

WATERMAIN ADJUSTMENT DETAIL




All Fittings Will Be Mechanical Joints With Retainer Glands.

PAID AS BITUMINOUS

SHOULDER, 13"

Proposed Sanitary Sewer To Be Constructed Of Ductile Iron Pipe Class 52 And Shall Extend A Minimum Of 10'-0" Either Side Of The Adjusted Watermain And Paid As Storm Sewer.



CONTRACT NO. 62700

TOTAL SHEET SHEETS NO.

LAKE 554 317


COUNTY

*(L-2[W,R];6,6A & 6 EXT) WRS-1


FED. ROAD DIST. NO. | ILLINOIS FED. AID PROJECT

866

MAILBOX ON NEARSIDE OF ENTRANCE, CURB AND GUTTER SECTION



MAILBOX ON FARSIDE OF ENTRANCE, SHOULDER SECTION



8' 3' . 5' .

MAILBOX TURNOUT DETAIL

47. Stope VARIES 5 6 7 3

SECTION B-B

N\ms\pignset\det-MT.dgn

7/2009 2:34:57 PM